

Cam-Loc Fittings

The Schumacher Aluminum Cam-Loc fittings are specially designed for high tensile strength, lightness and rigidity. The ease in which Cam-Loc fittings connect and disconnect make them ideal for both suction and discharge hoses.

Cam lock fittings are available with hose barbs or with male or female pipe thread. Custom Cam-Loc fittings are also available.





Applications:

- Agriculture
- Chemicals/Petroleum
- Construction
- Material Handling

Material Options:

- Aluminum
- Brass
- Nylon
- Stainless Steel
- Polypropylene



Dimenions	Size	Fem I.D. /Male O.D.
 I.D.	1/2"	1.34"
	3/4"	1.34"
	1"	1-1/2"
	1-1/4"	1.89"
	1-1/2"	2.20"
	2"	2-1/2"
	2-1/2"	3"
 O.D.	3"	3-5/8"
	4"	4-3/4"
	5"	5-3/4"
	6"	6-15/16"
	8"	





Series	Size	Part Number	Weight	Max PSI
A	1/2"	9-5889	0.1	250
	3/4"	9-5890	0.1	250
	1"	9-5891	0.1	250
	1-1/4"	9-5892	0.2	250
	1-1/2"	9-5893	0.3	250
	2"	6-6918	0.4	250
	2-1/2"	6-6919	0.6	150
	3"	6-6920	0.7	150
	4"	6-6921	1.3	150
	5"	6-6922	1.6	75
	6"	6-6923	2.0	75
8"	6-6897	10.9	50	



Series	Size	Part Number	Weight	Max PSI
E	1/2"	9-5909	0.1	250
	3/4"	9-5910	0.1	250
	1"	9-5911	0.2	250
	1-1/4"	9-5912	0.3	250
	1-1/2"	9-5913	0.4	250
	2"	6-6900	0.6	250
	2-1/2"	6-6901	0.9	150
	3"	6-6902	1.3	150
	4"	6-6903	2.1	150
	5"	6-6914	3.6	75
	6"	6-6915	6.2	75
8"	6-6899	10	50	



Series	Size	Part Number	Weight	Max PSI
B	1/2"	9-5894	0.2	250
	3/4"	9-5895	0.2	250
	1"	9-5896	0.4	250
	1-1/4"	9-5897	0.6	250
	1-1/2"	9-5898	0.7	250
	2"	6-6936	0.9	250
	2-1/2"	6-6937	1	150
	3"	6-6938	1.6	150
	4"	6-6939	2.1	150
	5"	6-6940	3.3	75
6"	6-6941	5.0	75	



Series	Size	Part Number	Weight	Max PSI
F	1/2"	9-5914	0.1	250
	3/4"	9-5915	0.2	250
	1"	9-5916	0.2	250
	1-1/4"	9-5917	0.3	250
	1-1/2"	9-5918	0.5	250
	2"	6-6930	0.7	250
	2-1/2"	6-6931	1	150
	3"	6-6932	1.3	150
	4"	6-6933	2.3	150
	5"	6-6934	2.9	75
	6"	6-6935	3.9	75
	8"	9-6959	--	50



Series	Size	Part Number	Weight	Max PSI
C	1/2"	9-5899	0.2	250
	3/4"	9-5900	0.3	250
	1"	9-5901	0.4	250
	1-1/4"	9-5902	0.7	250
	1-1/2"	9-5903	0.7	250
	2"	6-6904	1	250
	2-1/2"	6-6905	1.3	150
	3"	6-6906	2.2	150
	4"	6-6907	3.2	150
	5"	6-6916	3.9	75
	6"	6-6917	7.7	75
	8"	6-6898	15.5	50



Series	Size	Part Number	Weight	Max PSI
DC	1/2"	9-5919	0.2	250
	3/4"	9-5920	0.2	250
	1"	9-5921	0.3	250
	1-1/4"	9-5922	0.6	250
	1-1/2"	9-5923	0.6	250
	2"	9-5924	0.8	250
	2-1/2"	9-5925	1	150
	3"	9-5926	1.3	150
	4"	9-5927	2.3	150
	5"	9-5928	3.1	75
	6"	9-5929	4.7	75
	8"	9-6832	9	50



Series	Size	Part Number	Weight	Max PSI
D	1/2"	9-5904	0.2	250
	3/4"	9-5905	0.2	250
	1"	9-5906	0.4	250
	1-1/4"	9-5907	0.7	250
	1-1/2"	9-5908	0.8	250
	2"	6-6924	0.9	250
	2-1/2"	6-6925	1.2	150
	3"	6-6926	1.8	150
	4"	6-6927	2.8	150
	5"	6-6928	3.4	75
	6"	6-6929	5.0	75
8"	6-9788	9.5	50	



Series	Size	Part Number	Weight	Max PSI
DP	1/2"	9-5930	0.1	250
	3/4"	9-5931	0.1	250
	1"	9-5932	0.1	250
	1-1/4"	9-5933	0.2	250
	1-1/2"	9-5934	0.3	250
	2"	9-5935	0.3	250
	2-1/2"	9-5936	0.5	150
	3"	9-5937	0.7	150
	4"	9-5938	1.2	150
	5"	9-5939	1.5	75
	6"	9-5940	2.5	75