

T-Bolt Hose Clamps

These heavy duty t-bolt hose clamps can be used for both agricultural and industrial usage. Main applications include agricultural irrigation hoses, vehicles, and the construction industry.



Zinc Plated

Advantages:

- Zinc plated band, bolt & nut provide high corrosion protection*
- High torque test
- Beveled band edges eliminates the chance of hose damage
- Smooth underside are gentle on hose & reduce the risk of leakage
- High tensile bolt ensures threads are not damaged even on repeated tightening.
- Heavy duty washers provides extra protection to the nut & bolt.
- Reinforced loops provides higher stability
- Hollow roller provides high uniform torque, plus protection to band
- 3 welding points provides increased security for larger sizes
- Uniquely designed bridge gives optimal hose protection
- Designed for sealing both suction & pressure hoses

Construction:

Bolt: T Head Grade 8.8

Available in ZINC PLATED, HYBRID, or ALL STAINLESS STEEL



All Stainless Steel

Diameter Size (mm)	Diameter Size (inches)	Part Number	Band Width (inches)	Band Thickness (inches)
26-28	1.02-1.10	3-0703	0.71	0.02
29-31	1.14-1.22	3-0704	0.79	0.03
32-35	1.26-1.38	3-0705		
36-39	1.42-1.54	3-0706		
40-43	1.57-1.69	3-0708		
44-47	1.73-1.85	9-5433	0.87	0.05
48-51	1.89-2.01	3-0709		
52-55	2.05-2.17	3-0710		
56-59	2.20-2.32	9-5434		
60-63	2.36-2.48	3-0712	0.95	0.06
64-67	2.52-2.64	3-0713		
68-73	2.68-2.87	3-0714		
74-79	2.91-3.11	3-0715		
80-85	3.15-3.35	3-0716		
86-91	3.39-3.58	3-0717		
92-97	3.62-3.82	9-5435		
98-103	3.86-4.06	3-0719		
104-112	4.09-4.41	3-0660		
113-121	4.45-4.76	3-0720		
122-130	4.80-5.12	3-0721		
131-139	5.16-5.47	3-0722		
140-148	5.51-5.83	3-0723		
149-161	5.87-6.34	3-0661		
162-174	6.38-6.85	3-0724		
175-187	6.89-7.36	3-0725		
188-200	7.40-7.87	3-0726		
201-213	7.91-8.39	3-0662		
214-226	8.43-8.90	3-0727		
227-239	8.94-9.41	3-0728		
240-252	9.45-9.92	3-0729		
256-268	10.08-10.55	6-9556		