

SCHUMACHER

IRRIGATION, INC.

Epoxy Coated Steel Fittings

Quality Underground & Aboveground Fittings

- Agricultural Irrigation
- Turf Irrigation
- Industrial Pipelines



Epoxy Coated Fittings



Epoxy Coated Steel Fittings

Schumacher Irrigation manufactures quality standard & custom-built epoxy coated steel fittings for agricultural, turf, & industrial applications. The Schumacher epoxy coating produces a one-piece bonded surface that provides excellent flow characteristics and is virtually impervious to weather and chemicals. The gasketed underground fittings require no solvent welding and less labor for project installations.

Standard & Custom-built Epoxy Fittings



Z, L, T, J, & Riser Valve Tees, Elbows, Tees, Service Tees, Crosses, Adapters, Manifolds, Christmas Trees, Surge Tanks, Sweep Elbow Extensions, Bolt-on Saddles, etc.

PVC Fittings

(for demanding water & soil conditions)
Z, L, T, J Pipes



Coupler/Connection Types & Sizes:

Plastic Irrigation Pipe Sizes (PIP)	6"-31"
Standard Iron Pipe Sizes (IPS)	3"-12"
Outside Diameter Sizes (OD)	2"-24"
Wedge-Tite (compression)	pip, ips, od
Metric	160-315 mm
Flanged	2"-24"
Ball & Socket	2"-12"
Ring Lock	3"-12"
Industrial Groove	2"-12"
Male/Female Threads	1/2"-8"

Wall thickness: 12ga .106" (standard); optional 10ga .135" or 7 ga .188"
Coating thickness: Standard is 4-6 mil, Double-coating is 8-12 mil

Schumacher Irrigation can provide the irrigation fittings to insure a successful installation.

SCHUMACHER

IRRIGATION, INC.

Telephone: 402-246-3685
Fax: 402-246-2072
E-Mail: irrigate@megavision.com
Website: www.megavision.com/schumacher

205 4th Street PO Box 289 Platte Center, Nebraska USA 68653