



Streamline 630 Series


The Ultimate Thinwall Dripperline for Medium Sized Fields of Seasonal Vegetables and Row Crops

Industry's Widest Flow Path

Wider cross-section allows large particles through short flow path.

Advanced Flap Technology

Systematically opens and closes during start-up and shut-down providing uninterrupted flow while open and preventing soil ingestion and root intrusion when closed.



Injection Molded Drippers

Welded into a seamless wall of tubing for added strength, durability and long-term performance.

TURBONET


Increased Flow Path Velocity

Commonly used turbulent drippers have overlapping tooth patterns, easily catching debris.

Turbonet Technology improves dripper performance by widening the tooth pattern, maximizing flow path velocity, allowing contaminants to pass easily through the dripper, virtually eliminating plugging.

Product Advantages

- Injection Molded Drippers - welded into a wall of seamless tubing preventing damage to the drippers during installation and distortion of the dripper flow even as tubing stretches and expands
- Seamless Construction
 - Stronger, more durable than comparable drippers
 - Fortifies against splitting or bursting under high pressures required for proper flushing
 - Eliminates root growth and intrusion - no path for roots to follow
- Dripperlines packaged with more feet per reel, the industry's longest, requiring fewer fittings and less time changing reels during installation
- Industry's lowest filtration requirement - 120 mesh
- Larger filter inlets, provide secondary filtration - reduces clogging, maintaining the essential supply of water to the dripper for constant delivery of water flow



Applications

- For sub-surface or surface installations.
- For peppers, tomatoes, melons and vegetable crops.
- **4 mil** – for seasonal use.
 - In light to medium textured soils with a minimum of rocks or clods – or under plastic mulch. Must be buried at least one inch under plastic.
- **6 mil** – for seasonal use, surface or shallow (up to 5") burial.
- **8 mil** – for seasonal or multi-seasonal use, surface or shallow (up to 8") burial.
- **10 mil** – for multi-seasonal use, surface or shallow (up to 10") burial.

Specifications

Wall thickness (mil): 4, 6, 8, 10


Inside diameter (inches): .636, .638

Nominal flow rates (GPH) @ 10 psi: .16, .22, .38

Common spacings: 8", 10", 12", 16", 18", 24"

Recommended filtration:

- 120 mesh for .22 and .38 GPH
- 140 mesh for .16 GPH



NETAFIM USA

5470 E. Home Ave. • Fresno, CA 93727


888.638.2346 • 559.453.6800

FAX 800.695.4753

www.netafimusa.com

Streamline 630 Series Technical Information

STREAMLINE Flow Rate vs. Pressure



DRIPPER DATA - 4, 6, 8 & 10 mil

| Dripper GPH | Exponent (x) | Constant (k) | Kd (630) | Cv |
|-------------|--------------|--------------|----------|------|
| 0.16 | 0.48 | 0.053 | 0.10 | .025 |
| 0.22 | 0.45 | 0.084 | 0.10 | .025 |
| 0.38 | 0.45 | 0.128 | 0.10 | .025 |

DRIPPER FLOW PATH DIMENSIONS

| Dripper | Length | Depth | Width |
|---------|--------|-------|--------|
| 0.16 | .905" | .018" | 0.020" |
| 0.22 | .504" | .020" | 0.021" |
| 0.38 | .504" | .026" | 0.026" |

PACKAGING DATA

| Wall | Reel Length | Weight | Reels per Pallet | Weight per Pallet |
|--------|-------------|--------|------------------|-------------------|
| 4 mil | 15,000' | 59 lbs | 16 | 989 lbs |
| 6 mil | 11,500' | 69 lbs | 16 | 1,149 lbs |
| 8 mil | 9,000' | 66 lbs | 16 | 1,101 lbs |
| 10 mil | 7,500' | 67 lbs | 16 | 1,117 lbs |

Packaging data using 22" x 11" cardboard reels with 1 1/2" hub hole.
Weights are approximate. 16 reels per pallet. Pallet weight includes 45 lbs. for weight of pallet.

MAXIMUM OPERATING PRESSURE

| Wall Thickness | psi |
|----------------|-----|
| 4 mil | 8 |
| 6 mil | 9 |
| 8 mil | 12 |
| 10 mil | 14 |

LENGTH OF RUN @ 0% Slope

0.16 GPH Dripper (0.16 @ 10 psi)

| Dripper Spacing | GPM per 100 ft. | Emission Uniformity (EU) | | |
|-----------------|-----------------|--------------------------|------|------|
| | | 94% | 92% | 90% |
| 8" | 0.398 | 391 | 472 | 538 |
| 12" | 0.267 | 535 | 650 | 743 |
| 16" | 0.201 | 670 | 813 | 929 |
| 18" | 0.177 | 731 | 888 | 1001 |
| 24" | 0.134 | 902 | 1093 | 1243 |

LENGTH OF RUN @ 0% Slope

0.22 GPH Dripper (0.24 @ 10 psi)

| Dripper Spacing | GPM per 100 ft. | Emission Uniformity (EU) | | |
|-----------------|-----------------|--------------------------|-----|-----|
| | | 94% | 92% | 90% |
| 8" | 0.586 | 310 | 377 | 420 |
| 12" | 0.394 | 427 | 515 | 583 |
| 16" | 0.296 | 528 | 640 | 724 |
| 18" | 0.260 | 580 | 698 | 792 |
| 24" | 0.197 | 715 | 860 | 976 |

LENGTH OF RUN @ 0% Slope

0.38 GPH Dripper (0.36 @ 10 psi)

| Dripper Spacing | GPM per 100 ft. | Emission Uniformity (EU) | | |
|-----------------|-----------------|--------------------------|-----|-----|
| | | 94% | 92% | 90% |
| 8" | 0.889 | 235 | 283 | 322 |
| 12" | 0.600 | 323 | 390 | 441 |
| 16" | 0.450 | 402 | 486 | 549 |
| 18" | 0.396 | 439 | 530 | 600 |
| 24" | 0.300 | 538 | 655 | 740 |

Netafim USA - Delivering Total Growing Solutions

- Dripplines • Filters • Valves • Air Vents • Sprinklers • Automation • Flow Meters

For Agriculture, Landscape, Greenhouse & Nursery



For more information call Netafim USA
Customer Service at (888) 638-2346.